

Technical Details

PREMIUM FLOW

Model	618PF	620PF	722PF	725PF	730PF	735PF	740PF
Cutting width	5.50 m (18 ft)	6.10 m (20 ft)	6.70 m (22 ft)	7.60 m (25 ft)	9.15 m (30 ft)	10.70 m (35 ft)	12.20 m (40 ft)
Number of belts	4	4	5	5	6	7	8
Belt length	550 mm	550 mm	500 mm	500 mm	500 mm	500 mm	500 mm
Table length	1.000 mm	1.000 mm	1.000 mm	1.000 mm	1.000 mm	1.000 mm	1.000 mm
Intake auger diameter	660 mm	660 mm	760 mm	760 mm	760 mm	760 mm	760 mm
Auger flight height	130 mm	130 mm	170 mm	170 mm	170 mm	170 mm	170 mm
Centrally supported auger	–	–	–	–	–	•	•
Belt drive	Mechanical by roller chain			Hydraulic, infinitely variable			
Rapeseed kit	• 2 counter acting side knives, 1,350mm, mechanical driven via the cutter bar			• 2 counter acting side knives, 1,350 mm, mechanical driven via knife drive with dog clutch, quick fit without tools, approx. 15 kg			
Crop dividers	• 2 short and foldable dividers			• 2 short and foldable dividers, quick fit without tools			
Cutting system	Schumacher EasyCut II cutting system with double guards and individually bolted sections with fine serration						
Guide rollers in place	○	○	•	•	•	•	•
Dual knife drive	–	–	–	–	–	•	•
Spare knife	•	•	•	•	•	•	•
Grain lifter	•	•	•	•	•	•	•
Split reel	–	–	–	–	–	–	•
Reel tines	Spring tines			Composite tines			
Multicoupler	•	•	•	•	•	•	•
Number of AHC sensors for automatic header control	2	2	3	3	4	4	4
Splash guard on rear wall	•	•	•	•	•	•	•
Weight	2,460 kg	2,620 kg	2,920 kg	3,140 kg	3,640 kg	4,290 kg	4,780 kg

• Standard ○ Option – not available